


CAM ACTION CLOSERS

Synergy Hardware Limited is one of the UK's leading distributors of door controls and architectural hardware. Whilst every effort has been made to ensure the information presented in this brochure is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice. © 2016 Synergy Hardware Limited






Doorways can prove difficult to negotiate for many, particularly for children, the disabled and the elderly. Countless doors use traditional controls which utilise a 'rack and pinion' mechanism to close the door. This type of closer can prove to be inefficient and cause the door to be heavy and challenging to open.

Cam action door closers from Synergy utilise highly efficient technology to ensure the door is easy to open, whilst retaining sufficient power to close the door.

The entire range is CE marked to BS EN 1154 and Certifire accredited by Exova (UK) Limited, who also independently tested all adjustable power models to attest to the fact that the mechanisms far exceed the requirements of BS:8300 and Approved Document M (ADM).

These very efficient door closers are available in four different models, catering for a host of performance and cost solutions. In addition, every model is available in a number of matching finishes resulting in the most comprehensive range of cam action door closers.





SNP Satin Nickel plated.



BRM Brown Bronze.



PCC Polished Chrome plated.



SESSilver coated.



PBM Polished Brass.

NOTE



\$1000 SERIES

CONCEALED CAM ACTION DOOR CLOSER. EN 2-4 POWER ADJUSTABLE BY SPRING.

- Compact concealed body, track and arm providing the ultimate aesthetic solution.
- Highly efficient cam action mechanism provides easy operation.
- Aluminium extruded body.
- 23mm wide slide track complete with matching arm.
- Adjustable closing speed and independent latch action.
- Cushion stop / backcheck with adjustment between 80° and 120° at installation..
- Fully reversible. Suitable for both door and transom mounted applications.
- Minimum door thickness: 44mm
- 777mm wide Minimum door width to enable the S1000 to meet the opening force requirements of ADM and BS8300 at EN3.



CE MARKED

- 1121-CPD-AD5192.
- DOP-SHL-DC61.




CERTIFIRE APPROVED

• CF 5293 up to FD60 on timber doors.



I E	SIE	טו ע) RS	EN	11.	5
3	8	$\frac{4}{2}$	1	1	3	


Closer with slide track and arm



ADDITIONAL OPTIONS

- Optional mechanical hold open device available (Not suitable for use on fire doors) with adjustment between 80° and 120° at installation.
- Optional intumescent packs are also available.

POWER CURVE



S3500 SERIES

SURFACE MOUNTED CAM ACTION DOOR CLOSER. EN 2-5 POWER ADJUSTABLE BY SPRING.

- Highly efficient cam action mechanism provides easy operation.
- Exclusive profile extruded body.
- Various finishes with matching slide track, arm and cover.
- Adjustable closing speed and independent latch action.
- · Adjustable backcheck function.
- Delayed action function.
- 860mm wide Minimum door width to enable the S3500 to meet the opening force requirements of ADM and BS8300 at EN3.
- 2 mechanism variants:
 \$3501 Door pull side mounted /
 Transom push side mounted.
 \$3506 Door push side mounted /
 Transom pull side mounted.
- 3 cover variants: Semi radius cover option. (S3501.SR or S3506.SR) Rectangular cover option. (S3501.RE or S3506.RE) Slide plate option. (S3501.MEC or S3506.MEC)



CE MARKED

- 1121-CPD-AD5199.
- DOP-SHL-DC75.



CERTIFIRE APPROVED


• CF 5312 up to FD120 on timber doors.



TESTED TO BS EN 1154



Closer with semi radius/ rectangular cover



Closer with slide plate





POWER CURVE



ADDITIONAL OPTIONS

- Optional mechanical hold open device available (Not suitable for use on fire doors) with adjustment at installation up to 150° depending on model and mounting application.
- Optional angle bracket available for push side fixing of the slide track to door frames with a deep reveal.





SNP Satin Nickel plated.



BRM Brown Bronze.



PCC Polished Chrome plated.



SESSilver coated.



PBM
Polished Brass.

NOTE





SNP Satin Nickel plated.



BRM Brown Bronze.



PCC Polished Chrome plated.



SESSilver coated.



PBM Polished Brass.

NOTE



S3400 SERIES

SURFACE MOUNTED CAM ACTION DOOR CLOSER. EN 2-4 POWER ADJUSTABLE BY SPRING.

- Highly efficient cam action mechanism provides easy operation.
- Exclusive profile extruded body.
- Various finishes with matching slide track, arm and cover.
- Adjustable closing speed and independent latch action.
- Adjustable backcheck function.
- 873mm wide Minimum door width to enable the S3400 to meet the opening force requirements of ADM and BS8300 at EN3.
- 2 mechanism variants.
 \$3401 Door pull side mounted /
 Transom push side mounted.
 \$3406 Door push side mounted /
 Transom pull side mounted.
- 3 cover variants:
 Semi radius cover option.
 (\$3401.SR or \$3406.SR)
 Rectangular cover option.
 (\$3401.RE or \$3406.RE)
 Slide plate option.
 (\$3401.MEC or \$3406.MEC)



CE MARKED

- 1121-CPD-AD5198.
- DOP-SHL-DC72.




CERTIFIRE APPROVED

• CF 5312 up to FD120 on timber doors.




I E	SIE	טו ע) RS	EN	11	5
4	8	$\frac{4}{2}$	1	1	3	

Closer with semi radius/rectangular cover



Closer with slide plate



ADDITIONAL OPTIONS

- Optional mechanical hold open device available (Not suitable for use on fire doors) with adjustment at installation up to 150° depending on model and mounting application.
- Optional angle bracket available for push side fixing of the slide track to door frames with a deep reveal.

POWER CURVE



S3000 SERIES

SURFACE MOUNTED CAM ACTION DOOR CLOSER. EN 3 FIXED POWER.

- Highly efficient cam action mechanism provides easy operation.
- Exclusive profile extruded body.
- Various finishes with matching slide track, arm and cover.
- Adjustable closing speed and independent latch action.
- 2 mechanism variants.
 \$3001 Door pull side mounted /
 Transom push side mounted.
 \$3006 Door push side mounted /
 Transom pull side mounted.
- 2 cover variants: Semi radius cover option. (S3001.SR or S3006.SR) Slide plate option. (S3001.MEC or S3006.MEC)



CE MARKED

- 1121-CPD-AD5197.
- DOP-SHL-DC70.



CERTIFIRE APPROVED


• CF 5312 up to FD120 on timber doors.




TESTED TO BS EN 1154



Closer with semi radius cover



Closer with slide plate





ADDITIONAL OPTIONS

- Optional mechanical hold open device available (Not suitable for use on fire doors) with adjustment at installation up to 150° depending on model and mounting application.
- Optional cushion stop available with adjustment between 80° and 120° at installation.
- Optional angle bracket available for push side fixing of the slide track to door frames with a deep reveal.





SNP Satin Nickel plated.



BRM Brown Bronze.



PCC Polished Chrome plated.



SES Silver coated.



PBM Polished Brass.

NOTE



T: 01902 893725 E: info@synergyhardware.co.uk
F: 01902 896746 W: www.synergyhardware.co.uk

Unit 2, Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP