

Surface Mounted Rack & Pinion Overhead Door Closer

S150.MEC

EN2-4 variable power by template door closer



- Die cast body
- Rack and Pinion mechanism with flat form armset
- Suitable for use in Fig 1 (Door Mount Pull) or Fig 6 (Door Mount Push) applications
- Adjustable closing speed and latch action (Latch in Fig.1 Only)
- Backcheck (Fig 1 Only)
- Tested in accordance with EN1154, suitable for the following door width / weight:
 - Fig 1 (Door Mount Pull) 850mm / 1100mm (40Kg / 80Kg)
 - Fig 6 (Door Mount Push) 950mm (60Kg)
- Maximum 105° Opening (All applications)

Technical Data



Declaration of Performance:
Available via our website



Certifire Certificate No.:
CF 5294



Classification:

Fig 1

3	8	4	1	1	3
---	---	---	---	---	---

Fig 6

3	8	3	1	1	3
---	---	---	---	---	---



Max. Tested Door Size / Weight:

Fig 1 (Door Mount Pull) -
1100mm / 80Kg

Fig 6 (Door Mount Push) -
950mm / 60Kg



CE Certificate No.:
2812 CPR-AD5191



Dimensions:
Available via our website

Available Body & Arm Finishes

Metallic Finishes



PSC

SES

SSN

RAL Colours and other plated finishes
available to Special Order – please see our
Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk www.synergyhardware.co.uk

Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.