

Concealed CAM Action Overhead Door Closer

S1000

EN2-4 power adjustable by spring concealed overhead door closer



- Extruded body
- High performance CAM action mechanism
- 23mm wide slide track with matching arm
- Maximum opening angle - 120°
- Adjustable closing, latching speed and track mounted cushion stop
- Mechanical hold open device available - NOT FOR USE ON FIRE RATED DOORS
- Suitable for use in door mount concealed position only
- Minimum door thickness 44mm
- Intumescent kit (S1000.INT) available separately for fitting into Timber fire rated door sets
- Tested in accordance with EN1154, suitable for the following door width / weight:
 - Door Mount Concealed - 850mm / 1100mm (40Kg / 80Kg)

Technical Data



CPR Declaration of Performance:

Available via our website



Certifire Certificate No.:

CF 5293



Classification:

Door Mount Concealed

3	8	4	1	1	3
---	---	---	---	---	---



CE Certificate Number:

2812 CPR-AD5192



Dimensions:

Available via our website

Available Track and Arm Finishes

Metallic Finishes



PCC

SES

SNP

RAL Colours and other plated finishes available to Special Order – please see our Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk www.synergyhardware.co.uk

Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.

