

Floor Springs

S4036

EN 3-6 Adjustable Power Floor Spring



- Suitable for double action doors only
- Compatible with Synergy double action strap sets
- Adjustable closing speed and latch speed
- Maximum tested door weight: 120Kg
- Maximum tested door width: 1400mm
- Tested in accordance with BSEN1154: 1997 and CE marked
- Suitable for use on 30 and 60 minute Timber fire rated doorsets
- Maximum tested opening angle: 105°
- Various extended spindle sizes available from 3 to 25mm
- Supplied complete with cover plate
- Mechanical hold open version available (NOT FOR USE ON FIRE RATED DOORSETS)

Technical Data



Declaration of Performance:
Available via our website



Classification:

3	8	6	1	1	4
---	---	---	---	---	---



CE Certificate No.:
2812-CPR-AD10790



Dimensions:
Available via our website

Available Accessory Pack Finishes

Metallic Finishes



PBM

SSS

SES

RAL Colours and other plated finishes available to Special Order – please see our Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk www.synergyhardware.co.uk

Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.

