

Concealed EN2-4 Cam Closer with 24vDC Electro-Magnetic Hold Open

S1000.EHO


EN2-4 power adjustable by spring door closer




- Door closer tested to EN1154, Track tested to EN1155 and complete unit tested to EN1634
- Aluminium extruded body
- High efficiency Cam action mechanism
- 31mm wide slide track with matching arm and integrated 24v DC Electro-magnetic hold open device with adjustable holding force from 25Nm to 78Nm
- Adjustable hold open point from 80° - 120°
- Requires 24vDC± 15% (0.058A / 1.4W) power supply from transformer and relay interface with Fire Alarm System
- Adjustable closing power, speed and latch action
- Minimum door thickness 44mm
- Intumescent packs available (S1000.EHO.INT)

Technical Data

 **Declaration of Performance:**
Available via our website

 **Certifire Certificate No.:**
CF 5293


 **Classification:**
EN1154

3	8	4	1	1	3
---	---	---	---	---	---

EN1155

3	8	4	1	1	3
---	---	---	---	---	---

CE Certificate No.:
1121-CPD-AD5192
1121-CPR-AD5019

 **Dimensions:**
Available via our website

Available Cover & Arm Finishes

Metallic Finishes



PCC SES SNP

RAL Colours and other plated finishes available to Special Order – please see our Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk
Fax: 01902 896746 www.synergyhardware.co.uk

Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.

