



# S300

## Surface mounted rack & pinion door closer EN 2-4 power adjustable by template

### Performance

- EN 2-4 adjustable power.  
(Fig.1 EN 2-4 / 1100mm maximum door width).  
(Fig.6 EN 3 / 950mm maximum door width).

- CE marked (DOP-SHL-DC53).

- Certifire approved up to FD120 on timber doors. 

- Tested to BS EN 1154 - Fig.1 

3	8	4	2	1	1	3
---	---	---	---	---	---	---

  
- Fig.6 

3	8	3	1	1	1	3
---	---	---	---	---	---	---

### Specifications

- Rack & Pinion mechanism with matching flat form armset.
- Extruded body.
- Universal application (Fig.1, Fig.6 & Fig.61).
- Adjustable closing speed and independent latch action.

### Models

S300 - Universal mounting (Fig.1, Fig.6 & Fig.61).

Add suffix **.SSR** for semi radius cover version.

Add suffix **.RE** for rectangular cover version.

Add suffix **.MEC** for slide plate option.


### Finishes

**SSN • SES • PSC • BRO**


(Page 48-51 for further details).

### Dimensions

Closer with semi-radius (.SSR) / rectangular (.RE) cover



Closer with slide plate (.MEC)



### Features

Fig.1 mounting.	✓
Fig.6 / Fig.61 mounting.	✓
Closing power EN size (Fig.1/Fig.6).	2-4 / 3
Adjustable closing speed and latch action.	✓
Optional mechanical hold open arm - Page 52. (Not CE marked or suitable for fire door applications).	S800.SES. HOA
Warranty.	10 years

2. RACK & PINION CLOSERS

S300 SR in PBM Finish

