



S4014

Floor spring EN 1-4 power adjustable by spring

Performance

- EN 1-4 adjustable power.
- CE marked (DOP-SHL-DC82).
- Tested to BS EN 1634-1 for FD30 and FD60 on timber doors.
- Tested to BS EN 1154 - [3][8][4-1][1][1][3]

Specifications

- Suitable for single and double action doors.
- Compatible with Synergy strap sets (Page 42-43).
- Adjustable closing speed and latch speed.
- Maximum door weight: 150kg.
- Maximum door width: 1100mm.
- Maximum door opening angle at 170°.
- Various spindle sizes available from 3 - 25mm.
- Supplied complete with cover plate.


Models

S4014 - Suitable for single and double action doors.

Finishes

PSS • SSS • PB • SB
(Page 48-51 for further details).

Dimensions



Features

Single action doors.	✓
Double action doors.	✓
Closing power EN size.	1-4
Adjustable closing speed and latch action.	✓
Maximum door weight.	150kg
Maximum door width.	1100mm
Maximum door opening angle.	170°
Optional mechanical hold open variant (not for fire doors).	S4014.HO
Extended spindle sizes available.	3-25mm
Conversion kit to suit Dorma cement box	S4014.DCK
Warranty.	10 years

