

Surface Mounted Rack & Pinion Overhead Door Closer

S300

EN2-4 power adjustable by template door closer



- Extruded Body
- Rack and Pinion mechanism with flat form armset
- Universal application (Fig 1, Fig 6 & Fig 61)
- Adjustable closing speed and latch action (Latch in Fig 1 Only)
- Backcheck (Fig 1 only)
- Tested in accordance with EN1154, suitable for the following door width / weight:
 - Fig 1 (Door Mount Pull) 850mm / 1100mm (40Kg / 80Kg)
 - Fig 6 (Door Mount Push) 950mm (60Kg)
 - Fig 61 (Frame Mount Push) 850mm / 1100mm (40Kg / 80Kg)
- Maximum 105° opening (All applications)
- Slimline Rectangular & Semi Radius cover options
- Genuine Stainless Steel material is used for all Stainless Steel Cover variants.

Technical Data



Declaration of Performance:
Available via our website



Certifire Certificate No.:
CF 5294



Classification:

Fig 1 / Fig 61

3	8	4	1	1	3
2					

Fig 6

3	8	3	1	1	3
---	---	---	---	---	---



CE Certificate No.:
2812 CPR-AD5193



Dimensions:
Available via our website

Available Cover & Arm Finishes

Metallic Finishes



PSC

SES

SSN

RAL Colours and other plated finishes available to Special Order – please see our Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk www.synergyhardware.co.uk
Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.

