

Surface Mounted High Efficiency CAM Action Overhead Door Closer

S3500

EN2-5 power adjustable by spring door closer



- Extruded body
- High performance CAM action mechanism
- Slide track with matching arm
- Adjustable closing speed and latch action
- Adjustable Backcheck and delayed action
- Mechanical Hold Open Device available - NOT SUITABLE FOR USE ON FIRE RATED DOORS
- Supplied in 2 variants; Pull side door/push side frame mounting (S3501) OR Push side door/pull side frame mounting (S3506)
- Maximum opening angle - 180° (S3501), 120° (S3506)
- Slideplate, semi-radius or rectangular cover options available

Technical Data



Declaration of Performance:

Available via our website



Certifiere Certificate No.:

CF 5312



Classification:

Door and Frame Mount Pull

4	8	5	1	1	3
---	---	---	---	---	---

Door and Frame Mount Push

3	8	5	1	1	3
---	---	---	---	---	---



Max. Tested Door Size / Weight:

Door and Frame Mount Pull -

1250mm / 100Kg

Door and Frame Mount Push -

1250mm / 100Kg



CE Certificate No.:

2812 CPR-AD5199



Dimensions:

Available via our website

Available Cover & Arm Finishes

Metallic Finishes



PCC

SES

SNP

RAL Colours and other plated finishes available to Special Order – please see our Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk www.synergyhardware.co.uk

Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.