

Surface Mounted Rack & Pinion Overhead Door Closer

S900

EN2-6 power adjustable by spring door closer



- Extruded Body
- Rack and Pinion mechanism with flat form armset
- Suitable for use in Fig 1 (Door mount pull) and fig 6 (door mount push) applications
- Adjustable closing speed and latch action
- Backcheck
- Tested in accordance with EN1154, suitable for the following door width / weight:
 - Fig 1 (Door Mount Pull) - 1400mm / 120Kg
 - Fig 6 (Door Mount Push) - 1250mm / 100Kg
- Maximum 180° Opening
- Slide plate or semi radius cover options
- Genuine Stainless Steel material is used for all Stainless Steel Cover variants

Technical Data



Declaration of Performance:
Available via our website



Certify Certificate No.:
CF 5294



Classification:

Fig 1

4	8	$\frac{6}{2}$	1	1	3
---	---	---------------	---	---	---

Fig 6

4	8	$\frac{5}{3}$	1	1	3
---	---	---------------	---	---	---



Tested Door Width / Weight Suitability:

Fig 1 (Door Mount Pull) -
1400mm / 120Kg

Fig 6 (Door Mount Push) -
1250mm / 100Kg



CE Certificate No.:
2812 CPR-AD5330



Dimensions:
Available via our website

Available Cover & Arm Finishes

Metallic Finishes



PSC SES SSN

RAL Colours and other plated finishes available to Special Order – please see our Finishes Brochures for further details

Synergy Hardware Limited

Tel: 01902 893725 sales@synergyhardware.co.uk www.synergyhardware.co.uk
Unit 2 Heath Mill Business Centre, Heath Mill Road, Wombourne, West Midlands WV5 8AP

E&OE. Whilst every effort has been made to ensure the information presented is correct, we can accept no responsibility for any errors that may exist. We also reserve the right to make alterations to the design or specification of any product without notice.